

AMENDMENTS TO THE CLAIMS:

This listing of the claims will replace all prior versions, and listings, of the claims in this application.

Claims 7, 18, 27, 29-70, 72-88 are canceled herein without prejudice or disclaimer.

Claims 1, 17 and 89-91 were previously canceled without prejudice or disclaimer.

Claims 98-99 are newly added.

Listing of Claims:

1. (Cancelled)
2. (Previously Presented) The method of claim 92, wherein the power level with which information is transmitted is selected in dependence on at least one of a parameter of the intended second station and the content of the information.
3. (Previously Presented) The method of claim 92, wherein the power level with which information is transmitted is selected in dependence on at least one of a parameter of the intended second station and the content of the information.
4. (Previously Presented) The method of claim 92, wherein said information is in the form of data packets.
5. (Previously Presented) The method of claim 92, wherein said information for a given second station includes information identifying the given station.
6. (Previously Presented) The method of claim 92, wherein a second mode of operation is provided in which the first station sends information to said second stations with substantially the same power level, one of said first and second modes being selected.

7. (Canceled)

8. (Previously Presented) The method of claim 6, wherein the controller is arranged to send a channel configuration message to the first station to control which of said first and second modes is be used.

9. (Previously Presented) The method of claim 8, wherein said first station is arranged to send a message to said controller advising the controller if it can perform the mode contained in the channel configuration message.

10. (Currently Amended) The method of claim ~~[[7]]~~92, wherein said controller is arranged to send a channel configuration message to the first station to advise the first station as to the range of power levels to be used to transmit information to the second stations.

11. (Currently Amended) The method of claim ~~[[7]]~~92, wherein values representing the power levels are sent to the first station by said controller, said values being mapped to the power levels which are used by said first station to transmit information to said second station.

12. (Currently Amended) The method of claim ~~[[7]]~~92, wherein said controller is a radio network controller.

13. (Previously Presented) The method of claim 92, wherein said first station is a base station.

14. (Previously Presented) The method of claim 92, wherein said second stations comprise mobile stations.

15. (Previously Presented) The method of claim 92, wherein said common CDMA channel is a forward access

16. (Previously Presented) A method of controlling power with which information is transmitted by a first station to a plurality of second stations on a common channel, different information being intended for different stations, said method comprising a first mode in which the information is transmitted with a same power and a second mode in which different powers are used for information intended for different second stations.

17. (Cancelled)

18. (Canceled)

19. (Previously Presented) The network of claim 94, wherein said power level is selected in dependence on at least one of a parameter of the intended second station and the content of the information.

20. (Previously Presented) The network of claim 94, wherein said controller is a radio network controller, said first station is a base station and said second stations are user terminals.

21. (Previously Presented) The network of claim 94, wherein information sent from said controller to the base station comprises said power information and said information for a second station.

22. (Previously Presented) The network of claim 94, wherein a second mode of operation is provided in which the first station sends information to said second stations with substantially the same power level, one of said first and second modes being selected.

23. (Currently Amended) The network of claim ~~[[22]]~~94, wherein the controller is arranged to send a channel configuration message to the first station to control which of said first and second modes is to be used.

24. (Previously Presented) The network of claim 22, wherein said first station is arranged

to send a message to said controller advising the controller if it can perform the mode contained in the channel configuration message.

25. (Previously Presented) The network of claim 94, wherein said controller is arranged to send a channel configuration message to the first station to advise the first station as to the range of power levels to be used to transmit information to the second stations.

26. (Currently Amended) The network of claim [[2]]94, wherein said information is in the form of data packets.

27. (Canceled)

28. (Currently Amended) The network of claim [[2]]94, wherein said information for a given second station includes information identifying the given station.

29-70. (Canceled)

71. (Currently Amended) The network of claim [[18]]94, wherein said power level is selected in dependence on at least one of a parameter of the intended second station and the content of the information.

72-88. (Canceled)

89-91. (Cancelled)

92. (Currently Amended) A method of controlling power with which information is transmitted by a first station to a plurality of second stations on a common CDMA channel, different information being intended for different stations, said method comprising the step of transmitting said information in said common CDMA channel, wherein said information intended for different second stations are transmitted at different power levels, and said first station receives information from a controller on the power with which information for a respective second station is to be transmitted.

93. (Previously Presented) A method of controlling power with which information is transmitted by a first station to a plurality of second stations on a common CDMA channel, different information being intended for different stations, said method comprising a first mode in which the information is transmitted with a same power and a second mode in which different powers are used for information intended for different second stations.

94. (Currently Amended) A network comprising a first station and a plurality of second stations, said first station being arranged to transmit different information intended for different second stations on a common CDMA channel, said first station having a mode of operation in which said first station is arranged to transmit information intended for different second stations on the common CDMA channel at different power levels, said network further comprising a controller which is arranged to supply power information to said first station as to the power to be used for said information.

95. (Previously Presented) A radio network controller for controlling power with which information is transmitted by a base station to a plurality of user terminals on a common CDMA channel, different parts of said information being intended for different user terminals, said controller being arranged to control the power levels of said different parts of said information intended for different user terminals.

96. (Currently Amended) A base station for transmitting information to a plurality of user terminals on a common CDMA channel, different parts of said information being intended for different user terminals, said base station being arranged to transmit said different parts of said

information in said common CDMA channel, wherein said different parts of said information intended for different user terminals are transmitted at different power levels, said base station being arranged to receive information as to the power to be used for said different parts of said information.

97. (Previously Presented) A user terminal for receiving information transmitted on a CDMA common channel, different parts of said information being intended for different user terminals, said different parts of said information on the common CDMA channel being at different power levels.

98. (New) A method of controlling power with which information is transmitted by a first station to a plurality of second stations on a common CDMA channel, different information being intended for different stations, said method comprising the step of transmitting said information in said common CDMA channel, wherein said information intended for different second stations are transmitted at different power levels, and said first station receives information from a controller on the power with which information for a respective second station is to be transmitted and said controller is arranged to send a channel configuration message to the first station to advise the first station as to the range of power levels to be used to transmit information to the second stations.

99. (New) A network comprising a first station and a plurality of second stations, said first station being arranged to transmit different information intended for different second stations on a common CDMA channel, said first station having a mode of operation in which said first station is arranged to transmit information intended for different second stations on the common CDMA channel at different power levels wherein a second mode of operation is provided in which the first station sends information to said second stations with substantially the same power level, one of said first and second modes being selected.